

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

MSDS code: 08058

1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

Application of the substance / the mixture Sealant

1.3 Details of the supplier of the safety data sheet

Manufacturer/Supplier:

Bryson Products Ltd
Redlands, Coulsdon, London CR5 2HT
Tel: 020 8660 9119
sales@bryson.co.uk

Further information obtainable from:

Bryson Products Ltd
Redlands, Coulsdon, London CR5 2HT
Tel: 020 8660 9119
sales@bryson.co.uk

1.4 Emergency telephone number:

During office hours tel.: +44 (0) 20 8660 9119. At all other times please contact your national poisoning centre.

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2 H319 Causes serious eye irritation.

Resp. Sens. 1 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sens. 1 H317 May cause an allergic skin reaction.

Carc. 2 H351 Suspected of causing cancer.

STOT SE 3 H335 May cause respiratory irritation.

STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure.

2.2 Label elements

Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

Hazard pictograms



GHS02 GHS07 GHS08

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 09.08.2016

Version number 5

Revision: 09.08.2016

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 1)

- **Signal word** Danger
- **Contains:**
diphenylmethanediisocyanate, isomers and homologues
- **Hazard statements**
 - H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
 - H332 Harmful if inhaled.
 - H315 Causes skin irritation.
 - H319 Causes serious eye irritation.
 - H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 - H317 May cause an allergic skin reaction.
 - H351 Suspected of causing cancer.
 - H335 May cause respiratory irritation.
 - H373 May cause damage to organs through prolonged or repeated exposure.
- **Precautionary statements**
 - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 - P251 Do not pierce or burn, even after use.
 - P284 In case of inadequate ventilation wear respiratory protection.
 - P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
 - P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
 - P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- **Supplemental information:**
EUH204 Contains isocyanates. May produce an allergic reaction.
- **2.3 Other hazards**
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

- **3.2 Mixtures**
- **Description:** Active substance with propellant

· **Dangerous components:**

CAS: 9016-87-9	diphenylmethanediisocyanate, isomers and homologues Resp. Sens. 1, H334; Carc. 2, H351; STOT RE 2, H373; Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2, H319; Skin Sens. 1, H317; STOT SE 3, H335	30- <50%
EC number: 911-815-4 Reg.nr.: 01-2119486772-26-xxxx	tris(2-chloro-1-methylethyl)phosphate Acute Tox. 4, H302	10- <20%
CAS: 115-10-6 EINECS: 204-065-8 Reg.nr.: 01-2119472128-37-xxxx	dimethyl ether Flam. Gas 1, H220; Press. Gas C, H280	5- <10%
CAS: 75-28-5 EINECS: 200-857-2 Reg.nr.: 01-2119485395-27-xxxx	isobutane Flam. Gas 1, H220; Press. Gas C, H280	1- <5%

(Contd. on page 3)

GB

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 2)

CAS: 74-98-6 EINECS: 200-827-9 Reg.nr.: 01-2119486944-21-xxxx	propane Flam. Gas 1, H220; Press. Gas C, H280	1- <5%
CAS: 36483-57-5 EINECS: 253-057-0	2,2-dimethylpropan-1-ol, tribromo derivative Eye Irrit. 2, H319; Aquatic Chronic 3, H412	1- <5%

• **Additional information:**

While curing the following substances are formed and released by a reaction with atmospheric humidity:

Carbon dioxide

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

• **4.1 Description of first aid measures**

• **General information:** Take affected persons out of danger area and lay down.

• **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

• **After skin contact:**

Immediately wash with water and soap and rinse thoroughly.

If symptoms persist consult doctor.

• **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

• **After swallowing:** Do not induce vomiting; call for medical help immediately.

• **4.2 Most important symptoms and effects, both acute and delayed**

No further relevant information available.

• **Information for doctor:** No further relevant information available.

• **Hazards** No further relevant information available.

• **4.3 Indication of any immediate medical attention and special treatment needed**

No further relevant information available.

SECTION 5: Firefighting measures

• **5.1 Extinguishing media**

• **Suitable extinguishing agents:**

CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

• **For safety reasons unsuitable extinguishing agents:** Water with full jet

• **5.2 Special hazards arising from the substance or mixture**

Formation of toxic gases is possible during heating or in case of fire.

Carbon monoxide (CO)

Carbon dioxide

Nitrogen oxides (NO_x)

Under certain fire conditions, traces of other toxic gases cannot be excluded, e.g.:

Hydrogen cyanide (HCN)

• **5.3 Advice for firefighters**

• **Protective equipment:** Wear self-contained respiratory protective device.

GB

(Contd. on page 4)

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 3)

SECTION 6: Accidental release measures

- **6.1 Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- **6.3 Methods and material for containment and cleaning up:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents
- **6.4 Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

SECTION 7: Handling and storage

- **7.1 Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Protect against electrostatic charges.
Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.
The usual precautionary measures are to be adhered to when handling chemicals.
- **7.2 Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Observe official regulations on storing packagings with pressurised containers.
- **Information about storage in one common storage facility:** Store away from water.
- **Further information about storage conditions:**
Store in cool, dry conditions in well sealed receptacles.
Protect from heat and direct sunlight.
- **7.3 Specific end use(s)** No further relevant information available.

SECTION 8: Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.
- **8.1 Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

WEL	Short-term value: 0.07 mg/m ³ Long-term value: 0.02 mg/m ³ Sen; as -NCO
-----	---

115-10-6 dimethyl ether

WEL	Short-term value: 958 mg/m ³ , 500 ppm Long-term value: 766 mg/m ³ , 400 ppm
-----	---

(Contd. on page 5)

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 4)

- **Additional information:** The lists valid during the making were used as basis.
- **8.2 Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**
The usual precautionary measures are to be adhered to when handling chemicals.
Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.
Do not inhale gases / fumes / aerosols.
- **Respiratory protection:**
This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.
- **Protection of hands:**



Protective gloves

- **Material of gloves**
Nitrile rubber, NBR
Recommended thickness of the material: ≥ 0.4 mm
Butyl rubber, BR
Recommended thickness of the material: ≥ 0.7 mm
- **Penetration time of glove material**
For the mixture of chemicals mentioned below the penetration time has to be at least 480 minutes (Permeation according to EN 374 Part 3: Level 6).
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Protective work clothing

SECTION 9: Physical and chemical properties

- **9.1 Information on basic physical and chemical properties**
 - **General Information**
 - **Appearance:**

Form:	Aerosol
Colour:	According to product specification
 - **Odour:** Characteristic
 - **Odour threshold:** Not determined.
- | | |
|---------------------------------------|-----------------------------|
| · pH-value: | Not determined. |
| · Melting point/Melting range: | Not applicable, as aerosol. |
| · Boiling point/Boiling range: | Not applicable, as aerosol. |
- **Flash point:** -97 °C

(Contd. on page 6)

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 09.08.2016

Version number 5

Revision: 09.08.2016

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 5)

· Flammability (solid, gaseous):	Not applicable.
· Ignition temperature:	
· Decomposition temperature:	Not determined.
· Self-igniting:	Product is not selfigniting.
· Danger of explosion:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
· Explosion limits:	
Lower:	3.0 Vol %
Upper:	18.6 Vol %
· Vapour pressure:	Not determined.
· Density at 20 °C:	1.06 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Insoluble.
· Partition coefficient (n-octanol/water):	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
VOC (EU)	179.5 g/l
VOC (EC)	16.90 %
· 9.2 Other information	No further relevant information available.

SECTION 10: Stability and reactivity

- **10.1 Reactivity** No further relevant information available.
- **10.2 Chemical stability**
- **Thermal decomposition / conditions to be avoided:**
No decomposition if used according to specifications.
- **10.3 Possibility of hazardous reactions** No dangerous reactions known.
- **10.4 Conditions to avoid** No further relevant information available.
- **10.5 Incompatible materials:** No further relevant information available.
- **10.6 Hazardous decomposition products:** No dangerous decomposition products known.

SECTION 11: Toxicological information

- **11.1 Information on toxicological effects**
- **Acute toxicity**
Harmful if inhaled.

(Contd. on page 7)

GB

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 6)

· **LD/LC50 values relevant for classification:**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

Oral	LD50	> 10000 mg/kg (rat)
Dermal	LD50	> 10000 mg/kg (rabbit)
Inhalative	LC50/4 h	1.5 mg/L (rat)

- **Primary irritant effect:**
- **Skin corrosion/irritation**
Causes skin irritation.
- **Serious eye damage/irritation**
Causes serious eye irritation.
- **Respiratory or skin sensitisation**
May cause allergy or asthma symptoms or breathing difficulties if inhaled.
May cause an allergic skin reaction.
- **CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**
- **Germ cell mutagenicity** Based on available data, the classification criteria are not met.
- **Carcinogenicity**
Suspected of causing cancer.
- **Reproductive toxicity** Based on available data, the classification criteria are not met.
- **STOT-single exposure**
May cause respiratory irritation.
- **STOT-repeated exposure**
May cause damage to organs through prolonged or repeated exposure.
- **Aspiration hazard** Based on available data, the classification criteria are not met.

SECTION 12: Ecological information

· **12.1 Toxicity**

· **Aquatic toxicity:**

9016-87-9 diphenylmethanediisocyanate, isomers and homologues

LC0/96 h	> 1000 mg/L (brachydanio rerio)
EC50/24 h	> 1000 mg/L (daphnia magna)
NOEC/21 d	> 10 mg/L (daphnia magna)

- **12.2 Persistence and degradability** No further relevant information available.
- **Other information:** The product is not easily biodegradable.
- **12.3 Bioaccumulative potential** No further relevant information available.
- **12.4 Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
Do not allow product to reach ground water, water course or sewage system.
Danger to drinking water if even small quantities leak into the ground.
- **12.5 Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **12.6 Other adverse effects** No further relevant information available.

GB

(Contd. on page 8)

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 7)

SECTION 13: Disposal considerations

- **13.1 Waste treatment methods**
- **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Cured product can be deposited together with domestic waste. Observe the specific related regulations of local authorities.

This material and its container must be disposed of as hazardous waste.

Do not allow product to reach sewage system or any water course.

Do not pierce or burn, even after use.

- **European waste catalogue**

16 05 04*	gases in pressure containers (including halons) containing hazardous substances
-----------	---

08 05 01*	waste isocyanates
-----------	-------------------

- **Uncleaned packaging:**

- **Recommendation:**

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

Disposal must be made according to official regulations.

SECTION 14: Transport information

- **14.1 UN-Number**

- **ADR, IMDG, IATA** UN1950

- **14.2 UN proper shipping name**

- **ADR** 1950 AEROSOLS

- **IMDG** AEROSOLS

- **IATA** AEROSOLS, flammable

- **14.3 Transport hazard class(es)**

- **ADR**



- **Class** 2 5F Gases.

- **Label** 2.1

- **IMDG, IATA**



- **Class** 2.1

- **Label** 2.1

- **14.4 Packing group**

- **ADR, IMDG, IATA** Void

(Contd. on page 9)

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 09.08.2016

Version number 5

Revision: 09.08.2016

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 8)

· 14.5 Environmental hazards:

· Marine pollutant: No

· 14.6 Special precautions for user

· Danger code (Kemler): Warning: Gases.

· EMS Number: -

· Stowage Code F-D,S-U

SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.

· 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category 2

· Tunnel restriction code D

· Remarks:
- Special provisions: 190, 327, 344, 625 (3.3)
- Special provisions for carriage: V14 (7.2.4); CV9, CV12 (7.5.11); S2 (8.5)

· IMDG

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Remarks:
- Special provisions: 63, 190, 277, 327, 344, 959 (3.3)

· IATA

· Remarks: - Special provisions: A145, A167, A802 (4.4)

· UN "Model Regulation":

UN 1950 AEROSOLS, 2.1

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

"CLP" Regulation (EC) No 1272/2008 (OJ L 353, 31.12.2008, p.1).

(Contd. on page 10)

GB

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 9)

"CHIP" Regulations SI 2009 No.716 (revoked 01.06.2015, only covering derogation period to 01.06.2017)

"REACH" Regulation (EC) No 1907/2006 (OJ L 396, 30.12.2006, p.1, with subsequent amendments).
 COMMISSION REGULATION (EU) 2015/830 of 28 May 2015

- **Directive 2012/18/EU**
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t
- **National regulations:**
- **Information about limitation of use:**
 Employment restrictions concerning juveniles must be observed.
 Employment restrictions concerning pregnant and lactating women must be observed.
- **Other regulations, limitations and prohibitive regulations**
- **Substances of very high concern (SVHC) according to REACH, Article 57** Not applicable.
- **15.2 Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant phrases**
 H220 Extremely flammable gas.
 H280 Contains gas under pressure; may explode if heated.
 H302 Harmful if swallowed.
 H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
 H335 May cause respiratory irritation.
 H351 Suspected of causing cancer.
 H373 May cause damage to organs through prolonged or repeated exposure.
 H412 Harmful to aquatic life with long lasting effects.
- **Previous Revision Date:** 13-04-2011 (UK)
- **Abbreviations and acronyms:**
 ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
 IMDG: International Maritime Code for Dangerous Goods
 IATA: International Air Transport Association
 GHS: Globally Harmonised System of Classification and Labelling of Chemicals
 EINECS: European Inventory of Existing Commercial Chemical Substances
 ELINCS: European List of Notified Chemical Substances
 CAS: Chemical Abstracts Service (division of the American Chemical Society)
 VOC: Volatile Organic Compounds (USA, EU)
 LC50: Lethal concentration, 50 percent
 LD50: Lethal dose, 50 percent
 PBT: Persistent, Bioaccumulative and Toxic
 SVHC: Substances of Very High Concern
 vPvB: very Persistent and very Bioaccumulative
 Flam. Gas 1: Flammable gases – Category 1
 Aerosol 1: Aerosols – Category 1
 Press. Gas C: Gases under pressure – Compressed gas
 Acute Tox. 4: Acute toxicity – Category 4

(Contd. on page 11)

Safety data sheet
according to 1907/2006/EC, Article 31



Printing date 09.08.2016

Version number 5

Revision: 09.08.2016

Trade name: Bryson Pro Series B1 Fire Rated Expanding Foam

(Contd. of page 10)

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

Resp. Sens. 1: Respiratory sensitisation – Category 1

Skin Sens. 1: Skin sensitisation – Category 1

Carc. 2: Carcinogenicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

· *** Data compared to the previous version altered.**

GB